

Please amend the Abstract on page 30 as follows:

~~The present invention relates to a~~ A mixed liquid separating apparatus for separating a particular substance from a mixed liquid containing at least two kinds of substances is provided ~~C and O of which follow rotating property is different.~~ The apparatus includes ~~It comprises~~ a cylindrical outer member [[1]], a rod-shaped inner member [[2]] and a driving unit ~~means~~ 3. The outer member ~~1~~ has includes an inducing port ~~11 for inducing the mixed liquid at one~~ at a first end thereof, and an expelling port ~~16 for expelling the separated particular substance O at other~~ at a second end thereof. ~~An~~ [[The]] inner member [[2]] is disposed coaxially with said ~~the~~ outer member [[1]] to be so as to be ~~relatively~~ rotatable relative to the cylindrical outer member thereto. At least one of an inner peripheral surface of the outer member and an outer peripheral surface of ~~[[said]]~~ the inner member [[2]] has a spiral guiding wall for guiding the particular substance [[O]] from the ~~[[one]]~~ first end to the ~~other second~~ end, by the relative rotation between ~~[[said]]~~ the outer member and ~~[[said]]~~ the inner member. ~~Thus, the~~ The particular substance [[O]] is separated during feeding to the ~~other second~~ end along the guiding wall.